

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01J 29/07	A1	(11) International Publication Number: WO 99/34391
		(43) International Publication Date: 8 July 1999 (08.07.99)

(21) International Application Number: PCT/IB98/01725


(22) International Filing Date: 29 October 1998 (29.10.98)

(30) Priority Data:
08/996,676 23 December 1997 (23.12.97) US(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).(71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7,
Kista, S-164 85 Stockholm (SE).(72) Inventors: LAKSHMANAN, Venugopal; Prof. Holstlaan 6,
NL-5656 AA Eindhoven (NL). BRANTJES, Con; Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL).(74) Agent: KOPPEN, Jan; Internationaal Octrooibureau B.V., P.O.
Box 220, NL-5600 AE Eindhoven (NL).(81) Designated States: JP, European patent (AT, BE, CH, CY, DE,
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).**Published***With international search report.*

(54) Title: COLOR CATHODE RAY TUBE WITH IMPROVED SHADOW MASK MOUNTING SYSTEM

(57) Abstract

An apertured shadow mask directs electron beams toward phosphor elements on the inside surface of the face plate of a CRT. The mask is fixed to a rectangular frame having corner brackets connected by light-weight diaphragm strips and resilient plates molded to the brackets. The resilient plates have holes toward the distal ends thereof which engage pins embedded in a skirt surrounding the face plate. The plates are precipitation hardened stainless steel having a thickness of 0.20 mm to 0.30 mm and provide sufficient spring force to retain the mask and frame as well as the internal magnetic shield which is fixed to the corner brackets by clips.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Color cathode ray tube with improved shadow mask mounting system.

BACKGROUND OF THE INVENTION.

his invention relates to a cathode ray tube (CRT) for color television and allied display applications, employing a shadow mask for color separation, and more particularly relates to such a CRT having an improved shadow mask mounting system..

5 RTs for color television, computer monitors and other display applications rely on a cathodoluminescent phosphor screen to provide a visible display. Such a screen is composed of a repetitive pattern of a large number of small red, blue and green-emitting phosphor elements, which are excited to luminescence by electron beams emanating from an electron gun behind the screen. There are three beams, one for each of the red, blue and green
10 components of a color display signal. In operation, the screen is repetitively scanned by the three beams simultaneously, while the intensities of the beams are modulated by the respective individual primary color components of the display signal. The large number of phosphor elements, together with the scanning frequency, results in the perception of a steady, full color display by a viewer.

15 Such CRTs typically employ a shadow mask to achieve color separation. A shadow mask is a thin sheet having a large number of apertures and mounted between the phosphor screen and the electron gun, a short distance behind the screen. The apertures are aligned with the phosphor elements on the screen and the electron beams are directed from the electron gun to converge at the mask. When the beams pass through the individual apertures,
20 they diverge from one another to land on the phosphor element of the corresponding color.

 The mask, which is typically 0.15 to 0.25 mm thick, is supported on a frame to maintain its shape. This frame is then securely mounted in the glass envelope in order to maintain the mask in proper registration with the screen. Such registration must not only be maintained in the X and Y directions, but also in the Z direction, i.e., along the tube axis in
25 order to insure that the beams do not land on adjacent phosphor elements, which would degrade the color purity of the display image.

 Particularly during the warm-up period, the mask heats up and expands in all directions. Once the frame also warms up, then the thermal compensation effect of the suspension system takes place, moving the whole mask closer to the screen, maintaining

overall color purity by bringing all of the mask apertures back into the electron beam path. When the temperature differential between the mask and frame is large during initial warm-up, the time required for thermal compensation is longer. This differential is minimized by using a frame of as low a mass as possible.

5 A common technique to maintain the proper Q space (distance between mask and screen) during tube warm-up has been to employ bimetal mounting springs attached to three sides of the frame, which springs are attached to mounting studs embedded in the wall of the glass envelope. As the mask heats and expands in the X, Y, and Z directions, the mounting springs also heat, and the different expansion rates of the component metals in the
10 springs produce a compensating motion of the entire mask toward the screen.

 A more recent design employs a so-called "corner lock" suspension system, in which corner lock mechanisms, each of which include thermal compensation means, are attached to the four corners of the frame. This results in a more stable arrangement than that achievable using the side mounting arrangement, thereby enabling use of a lighter and less
15 costly mask and/or frame.

 U.S. Patent Nos. 3,986,072 and 3,999,098, assigned to Zenith Radio Corporation, disclose corner lock systems wherein the frame is formed integrally with the mask, which is welded to four corner brackets. Cantilevered leaf springs welded to the corner brackets engage legs fixed to the face plate of the vacuum tube adjacent four corners of the
20 display screen. Three of the springs are provided with holes which engage studs on the legs, while a fourth spring is provided with a slot which engages a stud on the fourth leg. This slot permits movement of the mask in the X and Y directions (parallel to the screen) and fix it in the Z direction.

 The "frameless mask" of Zenith is formed in a complex shape in order to
25 provide the structural integrity to withstand compressive stresses for mounting without welding. However it is not sufficiently strong to support direct mounting of an internal magnetic shield to the corner brackets.

 The current Philips mask suspension system is described in an article by Robert Donofrio entitled "Corner Lock Suspension" in the Nov. 1995 issue of Information Display.
30 This system employs corner brackets welded to lightweight diaphragm strips to form a rectangular frame; each diaphragm strip has an angular cross section formed by a base section and an upright section to which the shadow mask is welded. A resilient plate, also referred to as a temperature compensating plate or as a hinge plate, is fixed to each corner plate by a spring which loads it toward a pin embedded in a corner of the skirt adjacent to the face plate.

The pin is engaged by a floating washer mounted to the hinge plate. During assembly, the floating washers are welded to the hinge plates after the mask/frame assembly is engaged to the pins. The phosphor elements are then applied in a photo-lithographic screening process which involves removing and replacing the assembly several times. After a conductive
5 coating is applied to the phosphor elements, the assembly is fixed in place by welding the floating washers to the studs. The internal magnetic shield is fixed in the vacuum envelope independently by separate links which are welded to the studs over the frame assembly.

U.S. Patent No. 4,652,792 of Toshiba discloses a rectangular frame which is suspended at its corners by spring members which provide geometric temperature
10 compensation during warm-up. The frame is 1.6 mm thick and therefore relatively heavy, and generates considerable scrap during manufacture insofar as it is stamped from a single piece and formed without seams.

A corner suspension system of Thompson Consumer Electronics is described in an article by R.C. Bauder and F.R. Ragland entitled "An Improved Shadow-Mask Support
15 System for Large-Size CRTs" in SID Intl. Technical Papers (1990). This system employs bimetal clips welded to the corners of a one-piece frame, and backward extending springs welded to the distal ends of the clips.

Drawbacks of the known systems include difficulty in salvaging masks and frames, where they are welded to the studs; high scrap rates during manufacture; complex
20 parts including bimetallic clips; inability to mount the IMS directly to the frame; or systems with heavy frames, which result in poor color purity from the long warm up times, and instability of the assembly when dropped.

SUMMARY OF THE INVENTION

25 According to the invention, the frame is a light weight frame with four diaphragm elements 0.2 to 0.4 mm thick welded to the corner brackets and resilient plates extending away from the display screen cantilever-fashion to engage the mounting pins embedded in the skirt. These plates provide the sole spring force for loading the plates against the pins, and this spring force provides the sole retention between the frame and the skirt. The
30 internal magnetic shield is attached directly to the corner brackets of the frame.

Since the plates are not welded to the pins, the material of the plates as well as its thickness and shape must be chosen to provide a spring force exceeding two pounds in order to withstand the shock incurred by dropping the CRT as well as long term thermal

cycling. In this regard a precipitation hardened stainless steel having a thickness of 0.20 mm to 0.30 mm and a trapezoidal shape has been found to be especially suitable.

The CRT according to the invention reduces the amount of scrap during manufacture, because the diaphragm strips are formed from strip stock, rather than stamping a rectangular shape and forming it.

If either the mask and frame or the face plate and skirt are found to be defective subsequent to assembly, the components can be readily dismantled for salvage, which also reduces scrap. Likewise, the internal magnetic shield can be readily detached from the frame.

Since separate springs are not required to achieve adequate retention force, the number of parts and therefore the number of manufacturing steps are reduced. Likewise, the elimination of welding steps for retaining the mask/frame and the magnetic shield simplifies manufacture. The chief advantage of eliminating welding, however, is improved salvageability of the components. A primary aspect of the invention is defined by claim 1, while the dependent claims define advantageous embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a section view of a cathode ray tube according to the invention,
Figure 2 is a plan view of the supporting frame and mask, seen from the rear,
Figure 3 is a partial perspective view of the corner bracket, frame, and mask exploded from the face plate;
Figure 4 is a plan view of a corner bracket and temperature compensating plate, seen from the front;
Figure 5 is a section view taken along line 5-5 of Figure 4;
Figure 6 is a plan view of a corner bracket and alternative embodiment of temperature compensating plate,
Figure 7 is a section view taken along line 7-7 of Figure 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figure 1, a color display tube includes a glass vacuum envelope 10 having a neck 11, a funnel 12, a substantially rectangular face plate 15, and a skirt 13 extending between the face plate and the funnel. Mounting pins 14 embedded in the skirt adjacent the four corners of the plate serve to position the color selection electrode or shadow mask 22 with respect to the display screen 18 on the inside surface of the face plate 15. The display screen 18 is composed of a large number of red, green and blue luminescing phosphor

elements which are covered with an aluminum coating 20. The elements luminesce when bombarded by electrons in the beams 21 emitted from an electron gun 20 mounted in the neck. The beams 21 are deflected by deflection coils 24 which are coaxially arranged about a longitudinal axis of the tube, and pass through apertures 23 in the mask 22 to illuminate the phosphor elements.

The mask 22 is welded to a supporting frame 25 which in turn is mounted on the pins 14. The frame 25 includes four corner brackets 26 connected by diaphragms 33 and 36, each bracket 26 having a resilient plate 40 welded thereto, the plates 40 being loaded against the pins 14 to position the mask 22 and frame 25 with respect to the vacuum envelope

10 According to the invention, an internal magnetic shield 52 is mounted directly to the corner brackets, in this example by dart clips 54. The shield 52 is connected to a metallic layer 57 on the inside of funnel 12 by spring loaded contact 56. This shields the electron beams from the earth's magnetic field and other interference.

Figure 2 is a plan view of the mask 22 and frame 25 seen from the rear, i.e., the side opposite the display screen. Two long diaphragms 33 and two short diaphragms 36, all having angled cross sections, are welded to the corner brackets 26 to form a rectangle. Each of the diaphragms 33, 36 has a thickness of 0.2 mm to 0.4 mm, which closely matches the 0.2 mm thickness of the mask and assures a uniform expansion of the assembly during warm-up. The mask and diaphragms are preferably low carbon steel; the corner brackets, which are 0.5

20 to 0.8 mm thick, are either low carbon steel, nickel plated low carbon steel, or stainless steel. The corner brackets 26 each have a rectangular hole 28 which receives a dart clip for retaining the internal magnetic shield 52 (Figure 1).

The resilient plates 40, which accommodate thermal expansion and are also referred to as temperature compensation plates, are welded to respective corner brackets 26 and extend toward the viewer as cantilevers. Three of the resilient plates 40 have round holes 42 which fix their corresponding corners in the Z direction, and also fix the entire mask diaphragm assembly in the X and Y directions. The fourth resilient plate has a slot 43 which fixes its corner in the Z direction, the position in the X and Y directions being fixed by the other three plates.

Figure 3 shows the assembly of mask and frame in greater detail. Each long diaphragm 33 is formed by a base portion 34 and an upright flange 35 which meet at a right angle. Each short diaphragm 36 is formed by a base portion 37 and an upright flange 38 which meet at a right angle. The base portions 34, 37 are welded to the base 27 of the corner bracket 26. The upright flanges 35, 38 serve as mounting means for the mask 22, which is

welded thereto. Only some of apertures 23 for directing the electron beams are shown. The resilient plate 40 is welded to the bracket 26 as shown in Figure 4, and is provided with a round aperture 42 which is aligned for mounting against the round head of pin 14 on the skirt 13. The handling ears 14 are designed for automated handling of the frame during
5 manufacture and are not germane to the present invention.

During manufacture, the corner brackets 26 and plates 40 are placed on an assembly block which serves as a positioning jig (not shown), and the plates are welded to the respective corner brackets. The diaphragms are then welded to the corner brackets 26, and the completed frame is removed from the assembly block. The shadow mask 22 is then welded to
10 the flanges 35, 38, and the assembly is placed in the skirt 13 with the plates 40 resiled so that the holes 42 and slot 43 engage respective pins 14. The assembly is now ready for screening.

Screening is a well known process in which a photosensitive coating for each of the colors is exposed through the mask and developed. First a coating for one color of luminescing phosphors is exposed, then the mask/frame is removed and the coating is
15 developed to leave the luminescing elements. Then a photosensitive coating for another color is coated over the elements, the mask/frame is replaced, and the coating is exposed through the mask. The mask/frame is removed and the coating developed. The process is repeated for the third color, then all of the phosphor elements are coated with a 200-500 nm thick layer of aluminum and the mask/frame is again replaced on the pins 14. The internal magnetic shield
20 52 (Figure 1) is then fixed to the frame by means of dart clips received through apertures 28, and the vacuum envelope 10 (Figure 1) is sealed to the skirt and evacuated.

Figure 4 is a plan view of the corner bracket 26 and resilient plate 40 which is welded thereto; Figure 5 is a section view. The two views will be discussed together.

Each bracket 26 comprises a flat base portion 27 from which lateral flanges 32
25 are formed at substantially right angles, and mounting flange 30 is formed at about forty-five degrees. The flange 30 is provided with a mounting tab 31 to which the plate 40 is welded at welds 41. The plate 40 extends rearward as a cantilever and provides the spring force for loading the holes 42 (and slot 43, Figure 2) against the pins.

Figure 6 is a plan view of an alternative embodiment of resilient plate 46 which
30 carries a slide plate 48 having a formed boss 49 which engages the respective pin. The slide plate 48 can move in the X-Y plane by virtue of tabs 50 received through slots 47 in the TC plate. During manufacture, the slide plates 48 are welded to the plate 46, after the diaphragms are welded to the brackets, when the frame is initially placed on pins. This assures precise alignment with the face plate, but entails additional parts.

Essential to the present invention are the choice of material, thickness, and shape of the resilient plates 40. These design considerations should be effective to load each plate against the respective pin with a force of at least two pounds, without being subject to fatigue over the life of the CRT. This is necessary to maintain alignment of the mask and frame with an internal magnetic shield fixed thereto, without welding the assembly to the skirt on the face plate.

The material of the resilient plates is preferably a precipitation hardened stainless steel such as Cartech Custom 450, Custom 455, 466, 17-7PH, etc. These steels consist mainly of Fe, Ni, Cr, and other additives as necessary to provide a yield strength between 50 and 300 ksi, preferably exceeding 200 ksi. The thickness is preferably 0.20 to 0.40 mm, and the shape is tapered to form a trapezoid substantially as shown. In the preferred embodiment a 17-7PH steel is used, and the trapezoid has parallel edges with lengths of 9 mm and 28 mm, and connecting edges with lengths of 24 mm.

For the alternative embodiment of TC plate 46 shown in Figures 5 and 6, the slide plate 48 is of like material as the plate 46, which is as for plate 40. In an alternative embodiment of the slide plate 48, it may be of regular stainless steel such as 304 or 305 which are composed of 18% CR and 8% and 12% N; respectively, the remainder being substantially Fe.

The foregoing is exemplary and not intended to limit the scope of the claims which follow.

CLAIMS:

1. A cathode ray tube comprising:
 - a vacuum envelope (10) having a neck (11), a funnel (12), a substantially rectangular face plate (15) with an inside surface, a skirt (13) extending between said face plate (15) and said funnel (12), and four pins (14) extending inward from said skirt (13) adjacent respective corners of said face plate (15),
 - a display screen (18) on said inside surface, said display screen (18) comprising a plurality of phosphor elements and an electrically conductive coating (20),
 - an electron gun assembly (20) arranged in said neck (11) for emitting electrons toward said display screen (18),
 - a substantially rectangular shadow mask (22) mounted adjacent to said display screen (18) and comprising a plurality of apertures (23) which direct electrons toward the phosphor elements, and
 - a substantially rectangular supporting frame (25) to which said shadow mask (22) is connected, said frame (25) comprising four corner brackets (26) connected by two long diaphragm elements (33) and two short diaphragm elements (36) having a thickness of 0.2 mm to 0.4 mm, and four resilient plates (40) fixed directly to respective corner brackets (26), each plate (40) having aperture means engaging a respective one of said pins (14) and being spring loaded thereagainst, said plates (40) providing the sole spring force for loading the plates (40) against the pins (14), said spring force providing the sole retention between said frame (25) and said skirt (13).
2. A cathode ray tube as in claim 1 further comprising an internal magnetic shield (52) attached directly to said corner brackets (26).
3. A cathode ray tube as in claim 1 wherein said resilient plates (40) are made of precipitation hardened stainless steel.
4. A cathode ray tube as in claim 2 wherein said steel has a yield strength exceeding 200 ksi.

5. A cathode ray tube as in claim 2 wherein said resilient plates (40) have a thickness of 0.2 mm to 0.3 mm.
- 5 6. A cathode ray tube as in claim 1 wherein each resilient plate (40) is loaded against said respective one of said pins (14) with a spring force exceeding two pounds.
7. A cathode ray tube as in claim 1 wherein three of said resilient plates (40) have aperture means consisting of a round hole (42), and a fourth one of said resilient plates has
10 aperture means consisting of an elongate slot (43) having a major axis which is coplanar with said round holes.
8. A cathode ray tube as in claim 1 further comprising four dart clips (54), each said corner bracket having a hole (28) receiving one of said dart clips to attach said internal
15 magnetic shield (52) to said supporting frame (25).
9. Cathode ray tube as in claim 1 wherein at least one of said aperture means comprises a floating washer.
- 20 10. A cathode ray tube as in claim 1 wherein each of said diaphragm elements has an angled cross section with a right angle bend extending between corner brackets.

1/5




FIG. 1

2/5




FIG. 2

3/5




FIG. 3

4/5




FIG. 5




FIG. 4

5/5




FIG. 7




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 98/01725

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H01J 29/07

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, TXTUS1, TXTUS2, TXTEP1, TXTGB1, TXTWO1

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5072151 A (P. SPINA), 10 December 1991 (10.12.91), column 2, line 56 - column 3, line 14, figures 3-7	1,3-7,10
A	--	2,8,9
Y	US 3986072 A (A. ADAMSKI), 12 October 1976 (12.10.76), column 9, line 59 - column 10, line 52, figures 3,6,7	1,3-7,10
A	--	2,8,9
A	EP 0654811 A1 (VIDEOCOLOR S.P.A.), 24 May 1995 (24.05.95), column 2, line 29 - line 39, figures 2-3	1-10
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 February 1999

Date of mailing of the international search report

04.03.1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Tomas Erlandsson

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 98/01725

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5218267 A (F.R. RAGLAND, JR.), 8 June 1993 (08.06.93), column 2, line 56 - line 66 --	1-10
A	US 4652792 A (K. TOKITA ET AL.), 24 March 1987 (24.03.87), column 4, line 7 - line 39, figure 4 -- -----	1-10

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/02/99

International application No.

PCT/IB 98/01725

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5072151 A	10/12/91	DE 4132781 A,C	08/04/93
US 3986072 A	12/10/76	CA 1049082 A	20/02/79
		DE 2636397 A	24/02/77
		FR 2321184 A,B	11/03/77
		JP 52022875 A	21/02/77
		NL 7608907 A	15/02/77
EP 0654811 A1	24/05/95	CN 1111393 A	08/11/95
		IT 1265203 B	31/10/96
		IT MI932460 D	00/00/00
		JP 7192646 A	28/07/95
US 5218267 A	08/06/93	NONE	
US 4652792 A	24/03/87	DE 3650388 D,T	29/02/96
		EP 0195357 A,B	24/09/86
		IN 164873 A	24/06/89
		JP 1954668 C	28/07/95
		JP 6085301 B	26/10/94
		JP 62002432 A	08/01/87
		CN 1015844 B	11/03/92
		JP 62126527 A	08/06/87